



## (SK) Tube hitching system

The hitching system is:

- Quick connection and disconnection of the hose to the tank.
- Easy to assemble by means of 4 bolts and two hydraulic hoses on the place of the existing valve.
- Operating with one double-acting valve.
- Does not leak during transportation, due to the distance of the valve to seal rubber is minimal.
- No bends which also does not lose suction.
- Less weight as a suction arm.
- When ordering, specify whether the system will be mounted to the left or right of the tank. We recommend, if possible, to mount it on the right.

For further information:

[https://www.kempmachines.com/agriculture/tube-hitching-system?\\_return=/agriculture](https://www.kempmachines.com/agriculture/tube-hitching-system?_return=/agriculture)

	Types	Description	Price
➤	<b>SK6</b>	6'' version; Complete with valve and hose wagon and male coupling (without 6'' suction hose)	€ 2.400,-
➤	<b>SK8</b>	8'' version; Complete with valve and hose wagon and male coupling (without 8'' suction hose)	€ 2.750,-

	Options	Description	Price
➤	<b>SK8-6</b>	Male coupling with 6'' hose adapter	€ 150,-
➤	<b>KEG</b>	Recommended mounting angle 20 °, otherwise this wedge	€ 120,-
➤	<b>SK-KAR</b>	Individual trolley with grommet and coupling	€ 450,-

