



(OKBD) Weed brush Duo

The double weed brush can be connected to (mini) loaders, (mini) excavator, tractor, forklift, as long as the minimum oil yield is 40L and the machine is equipped with a non-pressurized return.

The advantage of a double brush is that a larger surface can be brushed at the same time. The brushes have the same direction of rotation so that the dirt is drained on one side. A second advantage is that two brushes adapt better to uneven surfaces than one large brush, because both can oscillate independently.

- The weed brush is designed with an oscillating construction, so that the brush is ground-following, therefore it is not necessary to correct the height for irregularities of +/- 15 cm. At the same time, the angle of the brush can be adjusted by lifting the frame or lowering it for a more or less aggressive effect.
- The double weed brush is available as a fixed or hydraulically pivoting version. By using a hydraulic swivel function with the pivot point against the vehicle, a large swivel range is possible, namely 70 degrees to the left and to the right, so that the weed brush can reach far next to the vehicle and thus there is also a good view on the brush.
- The diameter of the brushes are 750 mm. Available with a brush made of sheet steel or steel cable.
- The brush can be operated with two hydraulic functions.
- Weight \pm 300 kg

For further information:

https://www.kempmachines.com/park/weed-brushes/double-weed-brush?_return=/park/weed-brushes

	Types	Description	Price
➤	OKBSD	Fixed version	€ 3.325,-
➤	OKBZD	Hydraulic swivel version	€ 3.825,-

	Options	Description	Price
➤	OKBF	Movable rubber flap	€ 300,-
➤	OKBE	Electric use of turning and swivelling with 1 function	€ 600,-
➤	OKBJ	Joystick with magnetic base and cable	€ 250,-
➤	OKBD1000	Brush 1000 mm, 44 bundles steel cable	€ 400,-

For attachment parts see pages 61-65.