



## (RVS) Rubber feed scraper (galvanised)

- Can swivel both left and right 70°, due to 2 cylinders. Because of this the feed won't accumulate and it is possible to swivel while driving.
- The rubber strip can oscillate relative to the mounting frame for good ground adaptation and uniform wear of the rubber.
- Heavy pivot point with Teflon coated bushings.
- Middle part of the bar behind the rubber is 140\*140\*8 mm.
- Available in 5 widths and 2 types

### For further information:

<https://www.kempmachines.com/rubber-scrapers/galvanised-rubber-feed-scraper?return=/rubber-scrapers>

RVSS	RVSL
For vehicles up to ± 2.000 kg	For vehicles up to ± 6.000 kg
Vehicles up to 1.600 mm width	Vehicles up to 2.600 mm width
Weight ± 260 kg	Weight ± 360 kg
Cylinders: 25*40*300	Cylinders: 35*50*350

	Types	Rubber	Price
➤	RVSS1844	1.800 x 400 x 40 mm	€ 2.025,-
➤	RVSS2244	2.200 x 400 x 40 mm	€ 2.075,-
➤	RVSS2544	2.500 x 400 x 40 mm	€ 2.200,-
➤	RVSL2555	2.500 x 500 x 50 mm	€ 2.650,-
➤	RVSL2855	2.800 x 500 x 50 mm	€ 2.750,-
➤	RVSL3255	3.200 x 500 x 50 mm	€ 2.900,-

	Options	Description	Price
➤	VH	Adjustable angles (manually)	€ 200,-
➤	VHV	Extra rubber strengthening (only with adjustable angles).	€ 125,-
➤	SV	Shock valve for impact protection	€ 125,-
➤	GT	Pilot operating non-return valve	€ 125,-
➤	SM	Throttle valve to control slewing	€ 100,-

For attachment parts see pages 61-65.