



(RVSKS) Rubber feed- and silage scraper

The all scraper. With this scraper; feed can be pulled up, the sand is pushed out of the silage, or moved. And muddy yards and snow can be removed.

- Equipped with 2 pivot points and 4 cylinders, therefore the scraper has a swing angle of 70°.
- The front cylinders are to scrape the yard and sand from the silage and the rear cylinders to scrape the feed. The scraper comes beside the tractor.
- When scraping the silage, it is possible to move the scraper out of the centre by the double pivots. Hereby it is possible to clean the silage further.
- The rubber can move relative to the frame for optimum ground adaptation and uniform wear of the rubber.
- Price exclusive attachment parts.
- The types RVSKS2244 and RVSKS2544 are standard equipped with the option VH.

For further information:

https://www.kempmachines.com/rubber-scrapers/rubber-feed--and-silage-scraper?_return=/rubber-scrapers

Types	Rubber	Price
➤ RVSKS2244	2.200 x 400 x 40 mm	€ 2.925,-
➤ RVSKS2544	2.500 x 400 x 40 mm	€ 2.975,-
➤ RVSKSL2855	2.800 x 500 x 50 mm	€ 3.175,-

	Options	Description	Price
➤ VH	Adjustable angles	€ 200,-	
➤ SV	Shock valve for impact protection (2x)	€ 250,-	
➤ GT	Pilot operating non-return valve (2x)	€ 125,-	
➤ 3-WEG	3-way ball valve (at one double-acting function on vehicle)	€ 150,-	
➤ 6/2	Electrical 6/2 hydraulic valve	€ 350,-	

For attachment parts see pages 61-65,