



## (BP) Bale spike

Bale spike for hay and bales of straw.

- The bale spike is equipped with three heavy teeth in welding bushes so that the spikes do not tear off the tube.
- The bale spike is standard delivered with a rack for several bales and a foldable safety rack.
- **Light version (PBL):** width 1500 mm, 1000 or 1.500 mm high, for build on mini loaders, light tractors and similar. Spike Ø 30 mm.
- **Heavy version (BPZ):** 1850 width and 1800 mm high, for mounting on wheel loaders, telehandlers, loaders and similar. Spike Ø 45 mm
- Working length 950 mm.
- Prices are without attachment parts.

Types	Description	Price
➤ <b>BPL1000</b>	Light version width 1500 mm, height 1000 mm up to 800 kg.	€ 925,-
➤ <b>BPL1500</b>	Light version width 1.500 mm width, height 1.500 mm, up to 800 kg	€ 1.025,-
➤ <b>BPZ1800</b>	Heavy version width 1850 mm, height 1800 mm, up to 1500 kg	€ 1.375,-

Options	Description	Price
➤ <b>EI</b>	Extra welding bush	€ 25,-
➤ <b>ETL</b>	Extra spike light type	€ 50,-
➤ <b>ETZ</b>	Extra spike heavy type	€ 80,-
➤ <b>BPH</b>	Spike hydraulic folding	€ 550,-
➤ <b>DHL</b>	Removable mounting parts	€ 150,-
➤ <b>BPVR</b>	Adjustable rack of 1.500 – 2.300, incl. 2 spikes	€ 250,-

For attachment parts see pages 59-63, more info [kempmachines.com](http://kempmachines.com)