



(RSVB) Rubber bucket scraper

Rubber bucket scraper quick connect to telehandler, front end loader, feeder or ground bucket.

- Weight ± 230 kg.
- **RSVBK** U-profile replace by hollow sections 180-180-8. Main hollow sections 8 mm i.o. 4 mm. Side hollow sections 6 mm i.o. 4 mm. The RSVBK is provided with a rubber strengthening at the end of the hollow sections.

Price:	Working width	Price
Dimension rubber strip		
• 2.200 x 400 x 40 mm	2.050 mm	€ 800,-
• 2.800 x 400 x 40 mm	2.600 mm	€ 900,-
• 2.800 x 500 x 50 mm	2.600 mm	€ 975,-
• 3.200 x 400 x 40 mm	3.000 mm	€ 1.025,-
• 3.200 x 500 x 50 mm	3.000 mm	€ 1.100,-
• RSVBK 2800 x 500 x 50 mm	2.600 mm	€ 1.495,-
• RSVBK 3200 x 500 x 50 mm	3.000 mm	€ 1.625,-
Optional:		
• Steel angle to clamp with top clamp of the bucket		€ 100,-
• Adjustable hollow sections for clamping the scraper to buckets with cutting knife		€ 275,-

Pay attention! The bucket must be at least 250 mm narrower than the working width due to the side hollow sections and backlash.

When ordering, please specify bucket width!

