



(BP) Bale spike

Bale spike for hay and bales of straw.

- The bale spike is equipped with three heavy teeth in welding bushes so that the spikes do not tear off the tube.
- The bale spike is standard delivered with a rack for several bales and a foldable safety rack.
- **Light version (PBL):** width 1500 mm, 1000 or 1.500 mm high, for build on mini loaders, light tractors and similar. Spike \varnothing 30 mm.
- **Heavy version (BPZ):** 1850 width and 1800 mm high, for mounting on wheel loaders, telehandlers, loaders and similar. Spike \varnothing 45 mm
- Working length 950 mm.
- Prices are without attachment parts.

Types	Description	Price
➤ BPL1000	Light version width 1500 mm, height 1000 mm up to 800 kg.	€ 925,-
➤ BPL1500	Light version width 1.500 mm width, height 1.500 mm, up to 800 kg	€ 1.100,-
➤ BPZ1800	Heavy version width 1850 mm, height 1800 mm, up to 1500 kg	€ 1.450,-

Options	Description	Price
➤ EI	Extra welding bush	€ 25,-
➤ ETL	Extra spike light type	€ 50,-
➤ ETZ	Extra spike heavy type	€ 80,-
➤ BPH	Spike hydraulic folding	€ 650,-
➤ DHL	Removable mounting parts	€ 150,-
➤ BPVR	Adjustable rack of 1.500 – 2.300, incl. 2 spikes (BPZ1800 only)	€ 250,-

For attachment parts see pages 60-64, more info:

<https://www.kempmachines.com/agriculture/bale-spike?return=/agriculture>