



(RVSKS) Rubber feed- and silage scraper

The *all scraper*. With this scraper; feed can be pulled up, the sand is pushed out of the silage, or moved. And muddy yards and snow can be removed.

- Equipped with 2 pivot points and 4 cylinders, therefore the scraper has a swing angle of 70°.
- The front cylinders are to scrape the yard and sand from the silage and the rear cylinders to scrape the feed. The scraper comes beside the tractor. When scraping the silage, it is possible to move the scraper out of the centre by the double pivots. Hereby it is possible to clean the silage further.
- The rubber can move relative to the frame for optimum ground adaptation and uniform wear of the rubber.

| | Types | Rubber | Price |
|---|-------------------|---------------------|-----------|
| ➤ | RVSKSS2244 | 2.200 x 400 x 40 mm | € 2.850,- |
| ➤ | RVSKSS2544 | 2.500 x 400 x 40 mm | € 2.900,- |
| ➤ | RVSKSL2855 | 2.800 x 500 x 50 mm | € 3.095,- |

| | Options | Description | Price |
|---|--------------|---|---------|
| ➤ | VH | Adjustable angles | € 200,- |
| ➤ | SV | Shock valve for impact protection (2x) | € 250,- |
| ➤ | GT | Pilot operating non-return valve (2x) | € 125,- |
| ➤ | 3-WEG | 3-way ball valve (at one double-acting function on vehicle) | € 150,- |
| ➤ | 6/2 | Electrical 6/2 hydraulic valve | € 350,- |

For attachment parts see pages 60-64, more info:

<https://www.kempmachines.com/rubber-scrappers/rubber-feed--and-silage-scraper?return=/rubber-scrappers>