



(RMS) Manure scraper

With the manure scraper, manure can be removed from slatted floors.

- The Manure scraper is standard equipped with a buck where the attachment parts are being attached to.
- The manure slide has a rubber that is 500 mm high and 50 mm thick.
- Optional: It is possible to order a rubber slide on top of the manure scraper, which makes it easier to remove the manure along walls.
- Completely galvanised.
- Weight RMS2900 ± 625 kg.

For further information:

<https://www.kempmachines.com/rubber-scrapers/manure-scaper?return=/rubber-scrapers>

	Types	Working width ±	Price
➤	RMS2000	2.000 mm en depth 1.200 mm	€ 2.375,-
➤	RMS2500	2.500 mm en depth 1.350 mm	€ 2.575,-
➤	RMS2900	2.900 mm en depth 1.500 mm	€ 2.875,-

	Options	Description	Price
➤	RMST	Rubber scraper on top	€ 950,-

For **attachment parts** see pages 61-65.



(RMSHV) Rubber scraper adjustable angles

- The Manure scraper is standard equipped with a buck where the attachment parts are being attached to.
- The RMSHVS (light version) is equipped with a rubber of 400 mm high and 40 mm thick.
- The RMSHVL/XL (heavy version) is equipped with a rubber of 500 mm high and 50 mm thick.
- Equipped with hydraulically adjustable corners, this allows you to adjust the width of the slide at any time, thus adapting it to different stables.
- Standard delivered with 4x oil hose.
- Completely galvanised.

For further information:

Types	Description	Weight	Price
➤ RMSHVS	Hydraulic adjustable angles (1.200 tot 2.400 mm)	325 KG	€ 3.425,-
➤ RMSHVL	Hydraulic adjustable angles (1.600 tot 3.500 mm)	450 KG	€ 4.200,-
➤ RMSHVLX	Hydraulic adjustable angles (2.500 tot 5.000 mm)	650 KG	€ 5.300,-

Options	Description	Price
➤ GLGT	For one double-acting valve: Synchronisation valve and non-return valve.	€ 300,-

For attachment parts see pages 61-65.