



## (RVS) Rubber feed scraper (painted)

- Can swivel both left and right 70°, due to 2 cylinders. Because of this the feed won't accumulate and it is possible to swivel while driving.
- The rubber strip can oscillate relative to the mounting frame for good ground adaptation and uniform wear of the rubber.
- Heavy pivot point with Teflon coated bushings.
- Comes with galvanized bar.
- Available in 5 widths and 2 types.

RVSABM	RVSAB
For vehicles up to ± 2.000 kg	For vehicles up to ± 6.000 kg
Vehicles up to 1.600 mm width	Vehicles up to 2.600 mm width
Weight ± 225 kg	Weight ± 340 kg
Cylinders: 25*40*300	Cylinders: 35*50*350

Types	Rubber	Price
➤ RVSABM1844	1.800 x 400 x 40 mm	€ 1.800,-
➤ RVSABM2244	2.200 x 400 x 40 mm	€ 1.875,-
➤ RVSABM2544	2.500 x 400 x 40 mm	€ 2.000,-
➤ RVSAB2555	2.500 x 500 x 50 mm	€ 2.350,-
➤ RVSAB2855	2.800 x 500 x 50 mm	€ 2.475,-
➤ RVSAB3255	3.200 x 500 x 50 mm	€ 2.600,-

Options	Description	Price
➤ VH	Adjustable angles by hand	€ 200,-
➤ SV	Shock valve for impact protection	€ 125,-
➤ GT	Pilot operating non-return valve	€ 125,-
➤ SM	Throttle valve to control slewing	€ 75,-
➤ VHV	Extra rubber strengthening (Only by adjustable angles).	€ 125,-

For attachment parts see pages 59-63, more info [kempmachines.com](http://kempmachines.com)