



## (BKZXL) Bale clamp XL

A robust grabber for if there are many bales must be moved.

- Heavy-duty mainframe in which plastic guiding strips are placed. Due to these strips, there is minimal wear, while sliding. There is no need to be lubricated
- Standard equipped with a rack for 2nd bale, pilot-operated non-return valve, and pressure relief valve.
- Cylinder dimensions 40 x 70 x 900 mm.
- Weld-on parts for tractors, wheel loaders, and telehandlers.
- Sliding tubes of the clamping arm made of 10 mm steel 52.
- Clamping tubes are bent out of one piece, 8 mm thick steel and extra stiffeners (25 mm strip) (1). Height of the clamping tube is 600 mm.
- Weight  $\pm$  595 kg.
- Double model. Clamping range 900-1800 mm, mechanical adjustable to 1.100 – 2.100 mm.
- Price with hoses and 'male' connection, without attachment parts.

For further information:

[https://www.kempmachines.com/bale-grabbers/heavy-bale-clamp-xl?\\_return=/bale-grabbers](https://www.kempmachines.com/bale-grabbers/heavy-bale-clamp-xl?_return=/bale-grabbers)

	Types	Clamping range	Price
➤	<b>BKZXL2500</b>	700 – 2.500	€ 4.300,-
➤	<b>BKZXL2600</b>	800 – 2.600	€ 4.200,-
➤	<b>BKZXL</b>	Double model	€ 6.400,-

For attachment parts see pages 61-65.