



## (KSLR) Silage scraper left and right

- Includes a rubber strip, so that the covering sheet isn't damaged.
- The slewing is hydraulically by means a double-acting cylinder.
- Because the silage scraper slews at the front, it is possible to scrape in little spaces and when you are not perpendicular to the silage.
- The pivot point consists of 2 rotary buses which are positioned far from each other, to be able to take up a lot of strength.
- Equipped with a pressure relief valve.

	Types	Working width (centre vehicle to end)	Price
➤	<b>KSLRS3500</b>	3.500 mm (light version)	€ 3.050,-
➤	<b>KSLRL3500</b>	3.500 mm (heavy version)	€ 3.450,-
➤	<b>KSLRL4000</b>	4.000 mm (heavy version)	€ 3.550,-

For attachment parts see pages 60-64, more info:

[https://www.kempmachines.com/rubber-scrapers/silage-scraper-left-and-right-hydraulic?\\_return=/rubber-scrapers](https://www.kempmachines.com/rubber-scrapers/silage-scraper-left-and-right-hydraulic?_return=/rubber-scrapers)



## (KSV) Silage scraper fixed

- The KSVS (light version): suitable for mini-loaders, is made of tube 140x140x7 mm and the rubber is 1.000 mm long.
  - Weight 3.500 mm ± 225 kg.
- De KSVL (heavy version): suitable for larger loaders, are made of tube 180x180x8 mm and the rubber is 1,400 mm long, with a weight of 325 kg

	Types	Working width (Centre vehicle to end)	Price
➤	<b>KSVS3000</b>	3.000 mm	€ 1.575,-
➤	<b>KSVS3500</b>	3.500 mm	€ 1.625,-
➤	<b>KSVL3500</b>	3.500 mm	€ 2.050,-
➤	<b>KSVL4000</b>	4.000 mm	€ 2.100,-

For left and right use, attachment parts are calculated twice.

For attachment parts see pages 60-64, more info:

[https://www.kempmachines.com/rubber-scrapers/silage-scraper-fixed?\\_return=/rubber-scrapers](https://www.kempmachines.com/rubber-scrapers/silage-scraper-fixed?_return=/rubber-scrapers)