



## (BKZXL) Bale clamp XL

A robust grabber for if there are many bales must be moved.

- Heavy-duty mainframe in which plastic guiding strips are placed. Due to these strips, there is minimal wear, while sliding. There is no need to be lubricated
- Standard equipped with a rack for 2nd bale and pilot-operated non-return valve.
- Cylinder dimensions 40 x 70 x 900 mm.
- Weld-on parts for tractors, wheel loaders, and telehandlers.
- Sliding tubes of the clamping arm made of 10 mm steel S2.
- Clamping tubes are bent out of one piece, 8 mm thickness steel and extra stiffeners (25 mm strip) (1).
- Weight  $\pm$  595 kg.
- Double model. Clamping range 900-1900 mm, mechanical adjustable to 1.100 – 2.100 mm.
- Price with hoses and 'male' connection, without attachment parts.

Types	Clamping range	Price
➤ <b>BKZXL2500</b>	700 – 2.500	€ 3.500,-
➤ <b>BKZXL2600</b>	800 – 2.600	€ 3.400,-
➤ <b>BKZXL2600</b>	Double model.	€ 5.200,-

Options	Description	Price
➤ <b>OV</b>	At working pressure above 225 bar, then install a pressure relief valve	€ 135,-

For attachment parts see pages 73-77, more info [kempmachines.com](http://kempmachines.com)