





(TenWK) Heavy yard scraper hydraulic short model

Extra short version with 3-point mounting parts.

- The right rubber scraper to clean your terrain and roads and remove snow (only for a front lift).
- Hydraulic 45° pivotable with 2 double-acting cylinders.
- The bar with the rubber of the scraper can be tilted relative to the frame, so there is always an optimum ground adaptation and uniform wear of the rubber.
- Delivered with rubber strip with steel inlay.
- Length of front rubber to centre lifting ball is 750 mm. This is 400 mm shorter than the regular TenW.
- Standard equipped with a shock valve.
- Weight TenWK2753 ± 350 kg.

For further information:

https://www.kempmachines.com/yard-scrapers/hydraulically-yard-scraper-short?_return=/yard-scrapers

| | Types | Rubber | Note | Price | |
|---|-----------|------------------|-------------|-----------|--|
| > | TENWK2753 | 2.700 x 500 x 32 | Adj. angles | € 2.750,- | |
| > | TENWK3053 | 3.000 x 500 x 38 | Adj. angles | € 2.950,- | |
| > | TENWK3253 | 3.200 x 500 x 38 | Adj. angles | € 3.075,- | |

| | Options | Description | | Price | |
|---|---------|----------------------------------|---|-------|--|
| > | GT | Pilot operating non-return valve | € | 125,- | |
| > | SK800 | For snow clearing: removable | | | |
| | | 800mm rubber shield | € | 950,- | |